Q.H. LIAO¹, S.R. HENCHER¹ and J.H. BLACK²¹University of Leeds, Department of Earth Sciences, Leeds LS2 9JT, UK²Golder Associates Ltd

Abstract

This paper presents the results from research to validate discrete fracture network modelling simulations of fractured reservoirs by comparison with conventional analytical solutions. Model rock masses containing layered formations and regular orthogonal fracture systems have been generated using the program FracMan. Pressure drawdown and build up tests have then been simulated for wells within the models using the software package Mafic. Pressure data generated from the discrete fracture network models have then been interpreted in terms of matrix block size and fractured reservoir system permeability. This has been done using standard analytical solutions within the well test interpretation programme (PIE). The interpreted data are compared to the input parameters used to define the numerical simulations. The sensitivity of reservoir behaviour to the various input data has been investigated with respect to matrix block size, permeability, pressure decline and influence radius of pseudo-steady state flow. The influence of changing permeability in fractures (k_f) and matrix blocks (k_m) on fractured reservoir system permeability (k_s) are investigated and described. The varying permeability within fractured reservoir has been proposed and a new method in combination of numerical simulation and analytical solution has been described for fractured reservoir with double porosity behaviour.

The results reported here give confidence that this combined research of simulated and analytical solutions have confirmed the importance of block size to fractured reservoir performance (single-phase flow), the strong influence of near field conditions to wellbore test results and various permeability definitions of fractured reservoir.