Th SP1 04

Spectral Element Simulation for Random Media

L. Hongjian* (Jilin University)

SUMMARY

The small-scale inhomogeneity is the random disturbance which is added to the average characteristics of media, and it is usually represented by a smooth spatial random process. By means of autocorrelation function, we produce normalized random disturbance with zero mean and reasonable variance. As we know, the spectral element method (SEM) combines the precision of pseudospectral method and the flexibility of finite-element method. Besides, by using the delaunay triangular mesh discretization and isoparametric transformation, SEM can deal with varied irregular mesh and improve the accuracy of process. In this work, we extend SEM to the case of complicated random medium and make some numerical Simulation. The results demonstrate a good effect.

Introduction

Generally underground media is inhomogeneous, it is usually represented by a smooth spatial random process. Ikelle, L et al (1993) proposed a method is to consider the direction of small-scale inhomogeneous body. Xi Xian et al (2005) studied the characteristics of stationary and non-stationary random medium and made forward modeling. Dimitri Komatitsch (1998) applied spectral element method (SEM) to simulate the seismic response of two-dimensional (2-D) and three-dimensional (3-D) geological structures. In this work, we extend SEM to the case of complicated random medium and make some numerical Simulation. The results demonstrate a good effect.

Method

Velocity and density of random medium at point (x, z) can be represented by the following equation.

$$\begin{cases} v(x, z) = v_0(1 + \sigma) \\ \rho(x, z) = \rho_0(1 + \sigma) \end{cases} \quad (1)$$

Where v_0 and ρ_0 are parameters of background medium, σ is the random disturbance.

Based on autocorrelation function $\phi(x, z)$ and autocorrelation length a, b , we calculate the power spectral function of the random process.

$$\phi(k_x, k_z) = \int_{-\infty}^{+\infty} \int_{-\infty}^{+\infty} \phi(x, z) e^{-i(k_x x + k_z z)} dx dz \quad (2)$$

From $-\pi$ to π , we generate a uniformly distributed two-dimensional random field and spectral function.

$$\psi(k_x, k_z) = \sqrt{\phi(k_x, k_z)} e^{i\theta(k_x, k_z)} \quad (3)$$

Perform an inverse fourier transform of $\psi(k_x, k_z)$

$$\psi(x, z) = \frac{1}{(2\pi)^2} \int_{-\infty}^{+\infty} \int_{-\infty}^{+\infty} \phi(k_x, k_z) e^{i(k_x x + k_z z)} dk_x dk_z \quad (4)$$

Calculate the mean and variance of random disturbance.

$$\begin{aligned} u &= \langle \psi(x, z) \rangle \\ d^2 &= \langle (\psi(x, z) - u)^2 \rangle \end{aligned} \quad (5)$$

Produce normalized random disturbance $\sigma(x, z)$ of zero mean and ε^2 variance.

$$\sigma(x, z) = \frac{\varepsilon}{d} [\psi(x, z) - u] \quad (6)$$

Based on $\sigma(x, z)$ and equation (1), the random media can be generated.

Examples

We combine the random media model with SEM (the material properties of random media are shown in table 1) and make some numerical Simulation. The size of global domain is 1200m*1200m. We place a source at the point (600m, 500m), the time function is Ricker wavelet with a dominant frequency of 200Hz. 201 receivers are evenly located at a horizontal line between 100m and 1100m at a depth of $z=500$ m. The Sampling interval is 0.01ms, it propagates for 2900 time steps (i.e. 29ms), then we will get the wave-field snapshots (shown in figure 2) and its seismogram records (shown in figure 3). Pick up some of them for research.

TABLE I: Material properties of random media

	Mean velocity	a	b	ε	Disturbance range
Parameters	3000 m/s	5m	5m	5%	25%

Figure 1(a) model of random media

Figure 1(b) Spectral element mesh

Figure 2(a) Wave-field snapshots at=14ms
receivers

Figure 2(b) Wave-field snapshots at=20ms
receivers

Figure 3(a) Seismogram record in the x direction

Figure 3(b) Seismogram record in the z direction

Conclusions

By means of autocorrelation function, we produce normalized random disturbance with zero mean and reasonable variance. It well meets actual geological conditions; we apply SEM to the model, the results prove that SEM seismogram records bring about a high degree of accuracy, clear reflection. When elastic wave encounter random media bodies, waveform event is continuous, effective signal generated by small random disturbance can be identified clearly.

References

- Ikelle, L., Yung, S., and Daube, F, 1993. 2-D random media with ellipsoidal autocorrelation functions, *Geophysics*, 58, 1359-1372
- Xi, X., Yao, Y, 2005. Non-stationary random medium model, *Oil Geophysical Prospecting*, 40, 71-75
- Dimitri, K., Jean-Pierre V, 1998. The Spectral Element Method: An Efficient Tool to Simulate the Seismic Response of 2D and 3D Geological Structures, *Bulletin of the Seismological Society of America*, 88, 368-392