Th SP2 05

Investigation and Model Correlations of V_p/v_s and Porosity of Carbonates

J. Pupos* (Montanuniversitaet Leoben) & N. Gegenhuber
(Montanuniversitaet Leoben)

SUMMARY

Many articles deal with the topic of compressional and shear wave velocity of carbonate rocks and their correlation as well as model correlations. This paper will show the first results of compressional and shear wave velocity measurements and the calculations using the model of Kuster & Toksoez.

Different carbonates of Austria were measured in the laboratory to determine their porosity as well as their compressional and shear wave velocity (dry). Two different measurements were executed to determine the effective porosity of samples (helium porosity and principle of Archimedes). Some samples have bigger helium porosity than the porosity that derived using the buoyance method. It was assumed that there are more pores with a radius under the radius of a water molecule, while they are big enough to let a helium molecule through.

Using the measured compressional/shear wave velocity and the effective porosity the inclusion model that developed by Kuster and Toksoez was accomplished for the dry samples. This model is limited to low porosity our result was sufficient. The penny shaped cracks with different aspect ratio (0.005-0.5) were used. It was observed, that different aspect ratios needed to be applied for different lithologies.

Introduction

Compressional and shear wave velocity of carbonates and their correlations are topics of many articles. Calculations with different models were carried out, like Kuster and Toksoez (1974) or the differential effective medium (DEM) theory for example by Zimmermann (1991). Xu and Payne (2009) give a new approach for model calculations for carbonates. An overview over different model approaches is given by Mavko et al (2011) and Schoen (2011). This paper will show the first results of compressional and shear wave velocity measurements and the calculations using the model of Kuster & Toksoez (1974) to demonstrate their correlations.

Measuring Method

In the laboratory porosity, compressional (v_p) and shear wave velocity (v_s) were determined. Effective porosity was measured using the principle of Archimedes. The effective helium porosity was determined using a helium-pycnometer. v_p and v_s were measured with an ultrasonic device. A signal from a signal generator is sent through the sample and the output signal is sent to a computer. A self-made program picks the first arrivals of v_p and v_s (Gegenhuber & Steiner-Luckabauer, 2012).

Model calculations- Kuster and Toksoez (1974)

Kuster and Toksoez (1974) is an inclusions model. The cavities implemented are isolated with respect to the flow suitable for ultrasonic laboratory measurements. The model is limited to low porosity.

$$k_{\text{KT}} = \left(k_s + \phi * \frac{\frac{4}{3} * \mu_s * (k_s - k_s)}{k_s + \frac{4}{3} * \mu_s} P \right)^{-1} \quad \mu_{\text{KT}} = \mu_s * \left(1 - \phi * Q * \frac{\zeta_s}{\mu_s - \zeta_s} \right) * \left(1 + \phi * Q * \frac{\mu_s}{\mu_s + \zeta_s} \right)$$

P , Q and ζ depend on the shape of the cracks and can be found in Mavko et al (2011) or Schön (2012). k_s and μ_s represent the solid matrix values for compressional and shear modulus. Φ is the porosity. Penny shaped cracks with different aspect ratios (0.005-0.5) were used. Values for the solid matrix are $k_s = 90$ GPa and $\mu_s = 35$ GPa. Grain density was taken from the measurements from the helium-pycnometer, where the mean value of the data is $\rho_m = 2.77 \text{ g cm}^{-3}$.

Results

Figure 1 plots the two determined porosities. It can be observed that in most cases the results of the helium pycnometer measurements reach higher values than the measured values by using the Buoyancy process.

Figure 1 Porosity from a helium pycnometer versus porosity measured with the principle of Archimedes for different carbonates. Dots represent the measured data.

This can be explained due to a difference in pore throats. We assume that in the majority of cases the pore throats are as big so the helium molecules can flow through but the water molecules are too big to enter to that pores. Therefore the radii of the frequent pore throats values are located between the radii of water and helium molecules. If radii of molecules are applied, it can be seen as followed (Edward, 1970):

$$r_{\text{H}_2\text{O}} < r_{\text{pore throats}} < r_{\text{He}} \quad 278\text{pm} < r_{\text{pore throats}} < 140\text{pm (Van der Waals)}$$

Most of the “Haupt”-dolomite samples come from the same area (Gaaden b. Mödling). Hence, a big difference of results could not be explained according to the geographical distance. The porosity of the “Dachstein”-limestone shows two groups: one which shows a nearly linear behaviour and another one which shows higher helium porosity. By now this cannot be explained.

Kuster and Toksoez model was carried out as an inclusion model. The spherical inclusions can be characterized by aspect ratio (α). The different aspect ratios (0.3, 0.1, 0.05, 0.005 and 0.015) are demonstrated in figure 2 that are determined by calculation v_p and v_s as a function of porosity for inclusion filled with gas/air. It can be observed that the “Dachstein”-limestone is characterized by $\alpha=0.1$ and 0.005. The “Wetterstein”-dolomite can be represented with an aspect ratio of 0.01. The “Hauptdolomit” scatter too much for choosing one aspect ratio.

Figure 2 Displayed is v_p and v_s for dry samples versus (effective) porosity, additionally displayed are the calculated lines from Kuster and Toksöz (1974) for different aspect ratios (0.1; 0.05; 0.025; 0.01; 0.005).

Conclusion

In this paper different carbonates of Austria were taken into account for modelling the correlation between compressional and shear wave velocity and effective porosity. Additionally a look was taken at the difference between effective porosity from measurements using the principle of Archimedes and the effective helium porosity. Out of the correlation between these two porosities an idea of the value for the pore throat radius was derived. For the correlation between compressional/shear wave velocity and effective porosity the model approach by Kuster and Toksoez (1974) were used. For different lithologies, different aspect ratios needed to be applied. Due to a possible different pore shape, two groups with two aspect ratios can be separated for the “Dachstein”-limestone. The “Haupt”-dolomite scatter too much, for using only one aspect ratio.

References

- Edward, J.T. [1970] Molecular volumes and the Stokes-Einstein equation. *Journal of Chemical Education*, **47**, 261-270.
- Gegenhuber, N. and Steiner-Luckabauer, C. [2012] V_p/V_s Automatic Picking of Ultrasonic Measurements and their Correlation of Petrographic Coded Carbonates from Austria, 74th EAGE Conference & Exhibition, Copenhagen, P372.
- Kuster, G. and Toksoez, M. [1974] Velocity and attenuation of seismic waves in two phase media: part 1. Theoretical formulation. *Geophysics*, **39**, 587-606.
- Mavko, G., Mukerji, T. and Dvorkin, J. [2011] *The Rock Physics Handbook*. Cambridge university press.
- Schoen, J.H. [2011] *Physical Properties of Rocks - a workbook*, Elsevier B.V.
- Xu, S. and Payne, M. [2009] Modeling elastic properties in carbonate rocks. *The Leading Edge*, **28**, 66-74.
- Zimmermann, R. [1991] Elastic moduli of a solid containing spherical inclusions. *Mechanics of materials*, **12**, 17-24.